







SIGORIA

HIGH PERFORMANCE DUST COLLECTORS



Installed Storm 500

- Wide range of filter medias available including spun bonded polyester (fitted as standard) anti-static spun bond polyester and nano web flame retardant cellulose
- Storm 500 unit fitted with a high powered 2.2kW 3 phase fan set to give a nominal air volume of 700m³/hr at 150mm wg
- Storm 650 and 800 units fitted a high powered 5.5kW 3 phase fan set
- Easy to remove and empty hook on bin at the base of the unit
- Pulse cleaning technology delivers on-line cleaning to provide constant extraction
- Mild steel construction assembled with powder coated panels and framework
- Optional extras include mounting the Storm unit on castors, a pre-wired DOL starter, compressed air filter regulator and integrated flexible arm



Model	dim	dim	dim	Inlet	Available	dbA @ 1M	dbA @ 1M	Compressed	
Reference	A	В	С	Dia	M²	Fan	Fan & Pulse	Airbar G	kg
Storm 500	1455	525	525	100	9-15	72.4	76.1	4.0	50
Storm 650	1610	525	525	125	12-20	72.4	76.1	4.5	60
Storm 800	1760	525	525	150	15-26	72.4	76.1	5.0	70

All noise levels taken at 1M free field range with standard 2.2kW fan fitted

Fan & Silencer



Pulse Clean



Storm Range







Dust Control Environmental Ltd

Unit 5, Hawthorn Court, Howley Park Road,

Morley, Leeds, LS27 OBN

T: 00 44 (0) 113 302 1220

F: 00 44 (0) 113 253 6727

E: sales@dcelimited.com

www.dustcontrolenvironmental.com









Distributed by: